PADMAX
FD2831-VS
8MP Vari-focal WDR Network Dome Camera

ویژگی های کلیدی

پشتیبانی از پروتکل ONVIF | پشتیبانی از3DNR | قابلیت روز و شب | لوکس نوری پایین | رزولوشن 8 مگاپیکسل | پشتیبانی از IK10,IP67

ورودی برق12 VDC/POE | نور مادون قرمز تا 40 متر | دمای کار کرد 30- تا 60+ | دارای WDR120db | پشتیبانی از Starlight

پشتیبانی ازDefog | دارای لنز موتورایز

Sensor	1/2.7", 8.0 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.008Lux @ F1.5
Lens Mount	C/CS, 2.7~13.5mm
Iris	Fixed
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>56dB
Defog	Digital Defog
WDR	120dB
Video Compression	H.265+, H.264+, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main stream: 3840 × 2160 (1 fps–20 fps) 2688 × 1520 (1 fps–25/30 fps) Sub stream: 704 × 576 (1 fps–25 fps) 704 × 480 (1 fps–30 fps)
HLC	Supported
BLC	Supported
OSD	Supported
Privacy Mask	Up to 4 areas
ROI	Up to 4 areas
Motion Detection	Up to 4 areas
Smart Features	motion detection; video tampering; tripwire; intrusion; illegal access;

General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, Motion detection, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection, RTSP Authentication, User Authentication
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP,ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G), API
Protection	IP67,IK10
Network	1 RJ45 10M/100M Base-TX Ethernet
Power	DC 12V±10%, PoE (IEEE 802.3af) Power consumption: Max 7.4W
Dimensions (L × W × H)	122 x 88.9 mm
Weight	0.47kg (1.04lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Casing	Metal