PADMAX
SD5432X-SI
4MP 32X Network PTZ Camera

ویژگی های کلیدی

پشتیبانی از پروتکل ONVIF پشتیبانی از سه استریم تصویر قابلیت روز و شب رزولوشن 4 مگاپیکسل پشتیبانی از IP67 IK10, پشتیبانی از Starlight

ورودی برق+ 24 VDC/POE نور مادون قرمز تا 150 متر پشتیبانی از صدا دمای کار کرد 40- تا 70+ پشتیبانی از Auto Tracking

قابلیت زوم اپتیکال32X پشتیبانی ازFace Detection دارای WDR120db

Sensor	1/2.8" 4.0 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.005Lux @ F1.6
Lens Mount	C/CS, 4.8 mm–154 mm
Iris	Auto
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>56dB
Defog	Digital Defog
WDR	120dB
Video Compression	H.265+, H.264+, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main stream: 4M/3M/1080p/1.3M/720p (1–25/30 fps) Sub stream 1: D1/CIF (1–25/30 fps) Sub stream 2: 1080p/1.3M/720p (1–25/30 fps)
HLC/BLC/ROI	Supported
Digital Zoom	16X
OSD	Supported
Privacy Mask	Up to 24 areas
Preset Speed	Pan: 400°/s; Tilt: 300°/s
Motion Detection	Up to 4 areas
Smart Features	motion detection; video tampering; tripwire; intrusion; illegal access; audio detection; Perimeter detection, Object Abandoned, Face detection

General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, Motion detection, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection, RTSP Authentication, User Authentication
Audio Compression	G.711, G.726
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G), API
Audio I/O	Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/1
Protection	IP67, IK10, TVS 6000V lightning surge protection
Network	1 RJ45 10M/100M Base-TX Ethernet
Power	DC 24V±10%, PoE+ (IEEE 802.3at) Power consumption: Max 22W
Dimensions (L x W x H)	332 x 190 mm
Weight	4.7kg (10.3lb)
Working Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
Casing	Metal